

Part number

CHIN 24



Bulkhead mounting housing, LS-TYPE series, with 2 levers, size "104.27"

Product description

| | |
|---------------------|---------------------------|
| Product type | Bulkhead mounting housing |
| Series | LS-TYPE |
| Closing type | With 2 levers |
| Size | Size 104.27 |
| Cable entry | Without cable entry |

Technical data

| | |
|--------------------------------|------|
| IP degree of protection | IP65 |
|--------------------------------|------|

Further technical details

| | |
|---|----------------|
| Weight | 98,00 g |
| Operating temperature range (min, max) | -40°C...+125°C |

Material properties

| | |
|------------------------------|--------------------------------------|
| Other materials | Lever: Polyamide (PA) Gasket: NBR |
| Colour | RAL 9005 black |
| RoHs conformity | Compliant |
| China RoHs - EFUP | E |
| REACH SVHC substances | No |

Approvals / Standards

| | |
|-----------------------|---------|
| Certifications | DNV, BV |
| UL | ECBT2 |
| cUL | ECBT8 |

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747163101 |
| eCl@ss 8.1 | 27440202 |
| ETIM 7.0 | EC000437 |

Packaging Information

| | |
|----------------------------------|-----------------------|
| Packaging length | 250,00 mm |
| Packaging height | 145,00 mm |
| Packaging width | 300,00 mm |
| Packaging weight | 1,96 kg |
| Packaging volume | 10,88 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 20 Pcs |
| Packaging EAN code | 8015747187626 |
| Sub-packaging weight | 0,49 kg |
| Sub-packaging description | Plastic packaging |
| Sub-packaging quantity | 5 Pcs |
| Sub-packaging EAN barcode | 8015747187633 |

Part number CHIN 24



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "104.27" LS-TYPE version

| <p>inserts: page</p> <p>CD 64 poles + ⊕ 51+53 *</p> <p>CT, CTS **) 64 poles + ⊕ 57 *</p> <p>CDD 108 poles + ⊕ 64+66 *</p> <p>CDE 46 poles + ⊕ 83+85 *</p> <p>CSH 24 poles + ⊕ 91+93 *</p> <p>CCE 24 poles + ⊕ 100+104 *</p> <p>CNE, CSE, JCNE, JCSE 24 poles + ⊕ 101 and 109 *</p> <p>CSS 24 poles + ⊕ 122+123 *</p> <p>CTE, CTSE **) 24 poles + ⊕ 129 *</p> <p>CMSE 10+2 (aux) poles + ⊕ 139 *</p> <p>CMCE 10+2 (aux) poles + ⊕ 138 *</p> <p>CX 4/8 poles + ⊕ 155 *</p> <p>MIXO 6 modules 160+195 *</p> <p>insert centre distance: 104 x 27 mm</p> <p>* refer to catalogue page CN.12</p> | <p> housings with double lever</p> | <p> hoods with 4 pegs</p> | | | | | | | | | | | | | | | | | | | |
|---|--|---|-------|--|----------------|---|--|-------------------|-----------|--|---|----------|-------|-------------------|-----------|-------------------|-----------|-------------------|-----------|-------------------|-----------|
| <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 50%; text-align: left;">description</th> <th style="width: 25%; text-align: left;">part no.</th> <th style="width: 25%; text-align: left;">entry</th> </tr> <tr> <td>bulkhead mounting housing, with 2 levers</td> <td>CHIN 24</td> <td>M</td> </tr> <tr> <td>surface mounting housing, high construction, with 2 levers</td> <td>MAPN 24.32</td> <td>32</td> </tr> </table> | description | part no. | entry | bulkhead mounting housing, with 2 levers | CHIN 24 | M | surface mounting housing, high construction, with 2 levers | MAPN 24.32 | 32 | | <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 50%; text-align: left;">part no.</th> <th style="width: 25%; text-align: left;">entry</th> </tr> <tr> <td>MHON 24.32</td> <td>32</td> </tr> <tr> <td>MFON 24.32</td> <td>32</td> </tr> <tr> <td>MHVN 24.32</td> <td>32</td> </tr> <tr> <td>MFVN 24.32</td> <td>32</td> </tr> </table> | part no. | entry | MHON 24.32 | 32 | MFON 24.32 | 32 | MHVN 24.32 | 32 | MFVN 24.32 | 32 |
| description | part no. | entry | | | | | | | | | | | | | | | | | | | |
| bulkhead mounting housing, with 2 levers | CHIN 24 | M | | | | | | | | | | | | | | | | | | | |
| surface mounting housing, high construction, with 2 levers | MAPN 24.32 | 32 | | | | | | | | | | | | | | | | | | | |
| part no. | entry | | | | | | | | | | | | | | | | | | | | |
| MHON 24.32 | 32 | | | | | | | | | | | | | | | | | | | | |
| MFON 24.32 | 32 | | | | | | | | | | | | | | | | | | | | |
| MHVN 24.32 | 32 | | | | | | | | | | | | | | | | | | | | |
| MFVN 24.32 | 32 | | | | | | | | | | | | | | | | | | | | |
| <p>**) only in the CHIN 24 enclosure</p> <p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p> <div style="text-align: center;"> </div> <p>dimensions shown are not binding and may be changed without notice</p> | <p>dimensions in mm</p> <p>CHIN 24</p> <p>MAPN 24.32</p> | <p>dimensions in mm</p> <p>MFON 24.32</p> <p>MFVN 24.32</p> <p>MHON 24.32</p> <p>MHVN 24.32</p> | | | | | | | | | | | | | | | | | | | |