

Part number

CVAP 16 LS



Surface mounting housing, V-TYPE series, with 1 lever, Pg21 cable entry, size "77.27", high construction, with metal cover

| Product description | |
|---|--|
| Product type | Surface mounting housing |
| Series | V-TYPE |
| Closing type | With 1 lever |
| Size | Size 77.27 |
| Cable entry | With cable entry Pg21 |
| Specification | High construction, with metal cover |
| Technical data | |
| IP degree of protection | IP65 |
| Further technical details | |
| Contact resistance | ≤ 3 mΩ |
| Weight | 1,00 g |
| Operating temperature range (min, max) | -40°C...+125°C |
| Conductors stripping length | 8 mm (6 mm for 2,5 mm ²) |
| Torque for main contact | M2,5: 0.4 Nm; 3.5 lb.in (0,5 x 3mm) |
| Tightening torque for PE connection | M4: 1,2 Nm, 10,6 lb.in (Ph2 or 1,0x5,5mm) |
| Tightening torque for fixing screws | M3: 0.5 Nm; 4.4 lb.in (0.5x3 mm) |

| Material properties | |
|----------------------------------|---------------------------------------|
| Other materials | Lever: Stainless steel Gasket: NBR |
| Colour | RAL 7040 grey |
| RoHs conformity | Compliant |
| China RoHs - EFUP | E |
| REACH SVHC substances | No |
| Approvals / Standards | |
| Certifications | DNV, BV |
| UL | ECBT2 |
| cUL | ECBT8 |
| General ordering information | |
| EAN13 code | 8015747149693 |
| ETIM 7.0 | EC000438 |
| Packaging Information | |
| Packaging description | Carton box |
| Packaging quantity | 10 Pcs |
| Packaging EAN code | 8015747248235 |
| Sub-packaging description | Plastic packaging |
| Sub-packaging quantity | 5 Pcs |
| Sub-packaging EAN barcode | 8015747248242 |