

Part number

CX 01 9VF



Female modular insert, Mixo Data series, D-SUB, 9 poles, 1 module, 5 A 50 V 0,8 kV 3, crimp, shielded

Product description

Product type	Modular insert
Series	Mixo Data
Connection type	D-SUB
Gender	Female
N. of poles	9 poles
Size	1 module
Specification	Crimp, shielded

Technical data

Current	5 A
Voltage	50 V
Rated impulse withstand voltage	0,8 kV
Pollution degree	3
Rated voltage according to UL/CSA	600V
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure

Further technical details

Characteristics according to EN 61984	5A 50V 0.8kV 3
Insulation resistance	≥ 10 GΩ
Weight	19,40 g
Operating temperature range (min, max)	-40°C...+70°C
UL 94 flammability rating	V-0

Material properties

Main material	Polycarbonate (PC)
Colour	RAL 7032 grey
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Reference standard	EN 61984:2009-06
---------------------------	------------------

General ordering information

EAN13 code	8015747095839
eCl@ss 8.1	27440205
ETIM 7.0	EC000438

Packaging Information

Packaging length	112,00 mm
Packaging height	95,00 mm
Packaging width	117,00 mm
Packaging weight	0,28 kg
Packaging volume	1,24 dm ³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747095877
Sub-packaging weight	0,03 kg
Sub-packaging description	Plastic bag
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747095884