

Part number

CX 02 HF



Female modular insert, Mixo series, crimp connection, 2 poles, 2 modules, 16 A 2900/5000 V 15 kV 3, with heat-shrinking tube

Product description		Material properties	
Product type	Modular insert	Main material	Polycarbonate
Series	Mixo	Colour	RAL 7032 grey
Connection type	Crimp connection	RoHs conformity	Compliant
Gender	Female	China RoHs - EFUP	E
N. of poles	2 poles	REACH SVHC substances	No
Size	2 modules	Approvals / Standards	
Specification	With heat-shrinking tube	Reference standard	EN 61984:2009-06
Technical data		Certifications	DNV
Current	16 A	General ordering information	
Voltage	2900 - 5000 V	EAN13 code	8015747150385
Rated impulse withstand voltage	15 kV	eCl@ss 8.1	27440205
Pollution degree	3	ETIM 7.0	EC000438
Rated voltage according to UL/CSA	600V	Packaging Information	
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	Sub-packaging weight	0,05 kg
Further technical details		Sub-packaging description	Plastic bag
Characteristics according to EN 61984	16A 2900/5000V 15kV 3	Sub-packaging quantity	1 Pcs
Insulation resistance	$\geq 10 \text{ G}\Omega$	Sub-packaging EAN barcode	8015747167895
Contact resistance	$\leq 1 \text{ m}\Omega$		
Weight	53,00 g		
Operating temperature range (min, max)	-40 °C ... +125 °C		
UL 94 flammability rating	V-0		



Part number

CX 02 HF



Catalogue drawings

CX 02 HM



CX 02 HM

