

Part number

# DPTCM 15



Male insert,D-SUB, crimp connection, 15 poles

| Product description                           |  | Material properties                 |                    |
|---|--|-------------------------------------|--------------------|
| <b>Product type</b>                           | Data connector   | <b>Main material</b>                | Polycarbonate (PC) |
| <b>Series</b>                                 | D-SUB  | <b>RoHS conformity</b>              | Compliant          |
| <b>Connection type</b>                        | Crimp connection                                       | <b>China RoHS - EFUP</b>            | E                  |
| <b>Gender</b>                                 | Male   | <b>REACH SVHC substances</b>        | No                 |
| <b>N. of poles</b>                            | 15 poles   | <b>General ordering information</b> |                    |
| <b>Size</b>                                   | DA-15  | <b>EAN13 code</b>                   | 8015747287296      |
| Technical data                                |  | Packaging Information               |                    |
| <b>Current</b>                                | 5 A  | <b>Sub-packaging description</b>    | Plastic bag        |
| <b>Voltage</b>                                | 50 V   | <b>Sub-packaging quantity</b>       | 1 Pcs              |
| <b>Rated impulse withstand voltage</b>        | 1  | <b>Sub-packaging EAN barcode</b>    | 8015747184687      |
| <b>Pollution degree</b>                       | 3  |                                     |                    |
| Further technical details                     |  |                                     |                    |
| <b>Characteristics according to EN 61984</b>  | With turned contacts: 7 A / with stamped contacts: 5 A |                                     |                    |
| <b>Insulation resistance</b>                  | ≥ 10 GΩ  |                                     |                    |
| <b>Weight</b>                                 | 6,00 g   |                                     |                    |
| <b>Operating temperature range (min, max)</b> | -55 °C ... +125 °C                                     |                                     |                    |
| <b>UL 94 flammability rating</b>              | V-0  |                                     |                    |