


Part number

KI 1634 RI5



Interlocked switched socket-outlet, KI series, 3 poles + PE, 3 h (red), 16 A, 380 ÷ 380 V, with compartment for modular units, 7 DIN-rail modules EN 60715

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | KI..RI5 |
| N. of poles | 3 poles +  |
| Clock position | 3 |
| Cable entry | Pg29 |
| Specification | With compartment for modular units, 7 DIN-rail modules EN 60715 |

Technical data

| | |
|--------------------------------|---------------------------|
| Current | 16 A |
| Voltage | 380V (50Hz.) 440V (60Hz.) |
| IP degree of protection | IP55 |

Further technical details

| | |
|--|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|---------------|-----------------------------|
| Colour | RAL 7035 grey, RAL 3000 red |
|---------------|-----------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747150897 |
|-------------------|---------------|

Part number

KI 1634 RI5



Catalogue drawings

