


Part number

KI 1644 RI5



Interlocked switched socket-outlet, KI series, 3 poles + PE, 4 h (yellow), 16 A, 100 ÷ 130 V, with compartment for modular units, 7 DIN-rail modules EN 60715

Product description	
Product type	Interlocked switched socket-outlet
Series	KI..RI5
N. of poles	3 poles + 
Clock position	4
Size	143x343 fixing plates FC xx53 TB
Cable entry	Pg29
Specification	With compartment for modular units, 7 DIN-rail modules EN 60715

Technical data	
Current	16 A
Voltage	100 ÷ 130 V
IP degree of protection	IP55

Further technical details	
Weight	1.720,00 g
Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10

Material properties	
Colour	RAL 7035 grey, RAL 1021 yellow
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d

Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4

General ordering information	
EAN13 code	8015747048378

Packaging Information	
Packaging length	400,00 mm
Packaging height	165,00 mm
Packaging width	170,00 mm
Packaging weight	1,72 kg
Packaging volume	11,22 dm ³
Packaging description	Carton box
Packaging quantity	1 Pcs
Packaging EAN code	8015747114264

Part number

KI 1644 RI5



Catalogue drawings

