


Part number

# KI 1663 IB6



Interlocked switched socket-outlet, IB6 series,  
2 poles + PE, 6 h (blue), 16 A, 200 ÷ 250 V,  
sectionable fuse carrier 10 x 38 mm

#### Product description

<b>Product type</b>	Interlocked switched socket-outlet
<b>Series</b>	KI...IB6
<b>N. of poles</b>	2 poles + 
<b>Clock position</b>	6
<b>Size</b>	114x228 fixing plates FC xx41 TB
<b>Cable entry</b>	M25
<b>Specification</b>	Sectionable fuse carrier 10 x 38 mm

#### Technical data

<b>Current</b>	16 A
<b>Voltage</b>	200 ÷ 250 V
<b>IP degree of protection</b>	IP66

#### Further technical details

<b>Weight</b>	1.110,00 g
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C
<b>IK rating (impact degree of protection)</b>	IK10

#### Material properties

<b>Colour</b>	RAL 7035 grey, RAL 5015 blue
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	F6799547-ab84-42f2-938f-233ba663766d

#### Approvals / Standards

<b>Reference standard</b>	EN 60309-1, -2 e -4
---------------------------	---------------------

#### General ordering information

<b>EAN13 code</b>	8015747059572
-------------------	---------------

#### Packaging Information

<b>Packaging length</b>	520,00 mm
<b>Packaging height</b>	305,00 mm
<b>Packaging width</b>	490,00 mm
<b>Packaging weight</b>	16,65 kg
<b>Packaging volume</b>	77,71 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	15 Pcs
<b>Packaging EAN code</b>	8015747059640
<b>Sub-packaging length</b>	270,00 mm
<b>Sub-packaging height</b>	125,00 mm
<b>Sub-packaging width</b>	120,00 mm
<b>Sub-packaging weight</b>	1,11 kg
<b>Sub-packaging volume</b>	4,05 dm <sup>3</sup>
<b>Sub-packaging description</b>	Carton box
<b>Sub-packaging quantity</b>	1 Pcs
<b>Sub-packaging EAN barcode</b>	8015747059657