


Part number

KI 32114 RI5



Interlocked switched socket-outlet, KI series, 3 poles + PE, 11 h (red), 32 A, 440 ÷ 460 V, with compartment for modular units, 7 DIN-rail modules EN 60715

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7035 grey, RAL 3000 red
Series	KI..RI5		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + 	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Clock position	11	China RoHs - EFUP	50
Cable entry	Pg29	REACH SVHC substances	Yes Lead
Specification	With compartment for modular units, 7 DIN-rail modules EN 60715	SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Technical data		Approvals / Standards	
Current	32 A	Reference standard	EN 60309-1, -2 e -4
Voltage	440 ÷ 460 V	General ordering information	
IP degree of protection	IP55	EAN13 code	8015747048965
Further technical details		Packaging Information	
Weight	2.050,00 g	Packaging length	400,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Packaging height	165,00 mm
IK rating (impact degree of protection)	IK10	Packaging width	170,00 mm
		Packaging weight	2,05 kg
		Packaging volume	11,22 dm ³
		Packaging description	Carton box
		Packaging quantity	1 Pcs
		Packaging EAN code	8015747048972

Part number

KI 32114 RI5



Catalogue drawings

