


Part number

KI 3275 IB6



Interlocked switched socket-outlet, IB6 series, 3 poles + N + PE, 7 h (black), 32 A, 200/346 ÷ 240/415 V, sectionable fuse carrier 10 x 38 mm

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | KI...IB6 |
| N. of poles | 3 poles + N +  |
| Clock position | 7 |
| Cable entry | M25 |
| Specification | Sectionable fuse carrier 10 x 38 mm |

Technical data

| | |
|--------------------------------|-------------|
| Current | 32 A |
| Voltage | 480 ÷ 500 V |
| IP degree of protection | IP66 |

Further technical details

| | |
|--|-----------------|
| Weight | 1.000,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 9001 black |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747233743 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|-----------------------|
| Packaging length | 560,00 mm |
| Packaging height | 330,00 mm |
| Packaging width | 270,00 mm |
| Packaging weight | 10,00 kg |
| Packaging volume | 49,90 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 8 Pcs |
| Packaging EAN code | 8015747233750 |
| Sub-packaging length | 270,00 mm |
| Sub-packaging height | 125,00 mm |
| Sub-packaging width | 120,00 mm |
| Sub-packaging weight | 1,25 kg |
| Sub-packaging volume | 4,05 dm ³ |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747233767 |