

Part number

# KI 3295 IB6



Interlocked switched socket-outlet, IB6 series,  
3 poles + N + PE, 9 h (blue), 32 A, 200 ÷ 250  
V, sectionable fuse carrier 10 x 38 mm

| Product description                     |                                                                                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------------------|
| Product type                            | Interlocked switched socket-outlet                                                              |
| Series                                  | KI...IB6                                                                                        |
| N. of poles                             | 3 poles + N +  |
| Clock position                          | 9                                                                                               |
| Size                                    | 114x228 fixing plates FC xx41 TB                                                                |
| Cable entry                             | M25                                                                                             |
| Specification                           | Sectionable fuse carrier 10 x 38 mm                                                             |
| Technical data                          |                                                                                                 |
| Current                                 | 32 A                                                                                            |
| Voltage                                 | 200 ÷ 250 V                                                                                     |
| IP degree of protection                 | IP66                                                                                            |
| Further technical details               |                                                                                                 |
| Operating temperature range (min, max)  | -25°C ... +40°C                                                                                 |
| IK rating (impact degree of protection) | IK10                                                                                            |

| Material properties          |                              |
|------------------------------|------------------------------|
| Colour                       | RAL 7035 grey, RAL 5015 blue |
| Approvals / Standards        |                              |
| Reference standard           | EN 60309-1, -2 e -4          |
| General ordering information |                              |
| EAN13 code                   | 8015747199599                |