


Part number

KI 6365 RI5



Interlocked switched socket-outlet, KI series, 3 poles + N + PE, 6 h (red), 63 A, 346 ÷ 415 V, with compartment for modular units, 7 DIN-rail modules EN 60715

| Product description | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | KI..RI5 |
| N. of poles | 3 poles + N +  |
| Clock position | 6 |
| Size | 143x343 fixing plates FC xx53 TB |
| Cable entry | Pg29 |
| Specification | With compartment for modular units, 7 DIN-rail modules EN 60715 |

| Technical data | |
|--------------------------------|-------------|
| Current | 63 A |
| Voltage | 346 - 415 V |
| IP degree of protection | IP55 |

| Further technical details | |
|--|-----------------|
| Weight | 2.510,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

| Material properties | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 3000 red |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | F6799547-ab84-42f2-938f-233ba663766d |

| Approvals / Standards | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |

| General ordering information | |
|------------------------------|---------------|
| EAN13 code | 8015747049696 |

| Packaging Information | |
|------------------------------|-----------------------|
| Packaging length | 400,00 mm |
| Packaging height | 165,00 mm |
| Packaging width | 170,00 mm |
| Packaging weight | 2,73 kg |
| Packaging volume | 11,22 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 1 Pcs |
| Packaging EAN code | 8015747049702 |

Part number

KI 6365 RI5



Catalogue drawings

