

Part number

# MAPN 24.32



Surface mounting housing, LS-TYPE series, with 2 levers, M32 cable entry, size "104.27", high construction

#### Product description

<b>Product type</b>	Surface mounting housing
<b>Series</b>	LS-TYPE
<b>Closing type</b>	With 2 levers
<b>Size</b>	Size 104.27
<b>Cable entry</b>	With cable entry M32
<b>Specification</b>	High construction

#### Technical data

<b>IP degree of protection</b>	IP65
--------------------------------	------

#### Further technical details

<b>Weight</b>	444,00 g
<b>Operating temperature range (min, max)</b>	-40°C...+125°C

#### Material properties

<b>Other materials</b>	Lever: Polyamide (PA) Gasket: NBR
<b>Colour</b>	RAL 9005 black
<b>RoHs conformity</b>	Compliant
<b>China RoHs - EFUP</b>	E
<b>REACH SVHC substances</b>	No

#### Approvals / Standards

<b>Certifications</b>	DNV, BV
<b>UL</b>	ECBT2
<b>cUL</b>	ECBT8

#### General ordering information

<b>EAN13 code</b>	8015747163149
<b>eCl@ss 8.1</b>	27440202
<b>ETIM 7.0</b>	EC000437

#### Packaging Information

<b>Packaging length</b>	305,00 mm
<b>Packaging height</b>	180,00 mm
<b>Packaging width</b>	275,00 mm
<b>Packaging weight</b>	4,96 kg
<b>Packaging volume</b>	15,10 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	10 Pcs
<b>Packaging EAN code</b>	8015747250207
<b>Sub-packaging weight</b>	2,48 kg
<b>Sub-packaging description</b>	Plastic packaging
<b>Sub-packaging quantity</b>	5 Pcs
<b>Sub-packaging EAN barcode</b>	8015747187671

# Part number MAPN 24.32



Catalogue drawings



Catalogue drawings

**CH..N - MA, MF..N enclosures** size "104.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CD .....	64 poles + Ⓞ 51+53 *		
CT, CTS **)	64 poles + Ⓞ 57 *		
CDD .....	108 poles + Ⓞ 64+66 *		
CDE .....	46 poles + Ⓞ 83+85 *		
CSH .....	24 poles + Ⓞ 91+93 *		
CCE .....	24 poles + Ⓞ 100+104 *		
CNE, CSE, JCNE, JCSE	24 poles + Ⓞ 101 and 109 *		
CSS .....	24 poles + Ⓞ 122+123 *		
CTE, CTSE **)	24 poles + Ⓞ 129 *		
CMSE .....	10+2 (aux) poles + Ⓞ 139 *		
CMCE .....	10+2 (aux) poles + Ⓞ 138 *		
CX .....	4/8 poles + Ⓞ 155 *		
MIXO .....	6 modules 160+195 *		

insert centre distance: 104 x 27 mm  
\* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with 2 levers	<b>CHIN 24</b>	M		
surface mounting housing, high construction, with 2 levers	<b>MAPN 24.32</b>	<b>32</b>		
with pegs, side entry			<b>MHON 24.32</b>	<b>32</b>
with pegs, side entry, high construction			<b>MFON 24.32</b>	<b>32</b>
with pegs, side entry			<b>MHVN 24.32</b>	<b>32</b>
with pegs, side entry, high construction			<b>MFVN 24.32</b>	<b>32</b>

\*\*) only in the CHIN 24 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder  
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm

**CHIN 24**

**MAPN 24.32**

dimensions in mm

**MFON 24.32**

**MFVN 24.32**

**MHON 24.32**

**MHVN 24.32**