

Part number

# MFON 06 L25



Hood, LS-TYPE series, with 2 pegs, M25 side cable entry without adapter, size "44.27", high construction

#### Product description

<b>Product type</b>	Hood
<b>Series</b>	LS-TYPE
<b>Closing type</b>	With 2 pegs
<b>Size</b>	Size 44.27
<b>Cable entry</b>	Side cable entry M25
<b>Specification</b>	High construction

#### Technical data

<b>IP degree of protection</b>	IP65
<b>Further technical details</b>	
<b>Weight</b>	0,50 g
<b>Operating temperature range (min, max)</b>	-40°C...+125°C

#### Material properties

<b>Colour</b>	RAL 9005 black
<b>RoHs conformity</b>	Compliant
<b>China RoHs - EFUP</b>	E
<b>REACH SVHC substances</b>	No

#### Approvals / Standards

<b>Certifications</b>	DNV, BV
<b>UL</b>	ECBT2
<b>cUL</b>	ECBT8

#### General ordering information

<b>EAN13 code</b>	8015747163156
<b>eCl@ss 8.1</b>	27440202
<b>ETIM 7.0</b>	EC000437

#### Packaging Information

<b>Packaging length</b>	175,00 mm
<b>Packaging height</b>	195,00 mm
<b>Packaging width</b>	260,00 mm
<b>Packaging volume</b>	8,87 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	20 Pcs
<b>Packaging EAN code</b>	8015747187725
<b>Sub-packaging description</b>	Plastic packaging
<b>Sub-packaging quantity</b>	5 Pcs
<b>Sub-packaging EAN barcode</b>	8015747187695

# Part number MFON 06 L25



Catalogue drawings



Catalogue drawings

**CH..N - MA, MF..N enclosures**      size "44.27"      LS-TYPE version

<p>inserts:      page</p> <p>CDD ..... 24 poles + ⊕      59 *</p> <p>CQE ..... 10 poles + ⊕      80 *</p> <p>CSH ..... 6 poles + ⊕      88 *</p> <p>CCE ..... 6 poles + ⊕      94 *</p> <p>CNE, CSE, JONE, JOSE 6 poles + ⊕ 95 and 103 *</p> <p>CSS ..... 6 poles + ⊕      118 *</p> <p>CTE, CTSE **) ..... 6 poles + ⊕      126 *</p> <p>MIXO ..... 2 modules      160+195 *</p> <p>insert centre distance: 44 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p><b> housings with single lever</b></p>	<p><b> hoods with 2 pegs</b></p>
--	---	----------------------------------

description	part no.	entry
bulkhead mounting housing, with lever	<b>CHIN 06 L</b>	M
surface mounting housing, high construction, with lever	<b>MAPN 06 L32</b>	<b>32</b>
with pegs, side entry		
with pegs, side entry, high construction		
with pegs, top entry		
with pegs, top entry, high construction		

<p>**) only in the CHIN 06 L enclosure</p> <p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>	<p>dimensions in mm</p> <p><b>CHIN 06 L</b></p> <p><b>MAPN 06 L32</b></p>	<p>dimensions in mm</p> <p><b>MFON 06 L25</b></p> <p><b>MFVN 06 L25</b></p> <p><b>MHON 06 L25</b></p> <p><b>MHVN 06 L25</b></p>
---	---	---

dimensions shown are not binding  
and may be changed without notice