

Part number

MFON 24.32



Hood, LS-TYPE series, with 4 pegs, M32 side cable entry without adapter, size "104.27", high construction

Product description

Product type	Hood
Series	LS-TYPE
Closing type	With 4 pegs
Size	Size 104.27
Cable entry	Side cable entry M32
Specification	High construction

Technical data

IP degree of protection	IP65
Further technical details	
Weight	236,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747019330
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information

Sub-packaging weight	1,18 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187756

Part number MFON 24.32



Catalogue drawings



Catalogue drawings

CH..N - MA, MF..N enclosures size "104.27" LS-TYPE version

<p>inserts: page</p> <p>CD 64 poles + ⊕ 51+53 *</p> <p>CT, CTS **) 64 poles + ⊕ 57 *</p> <p>CDD 108 poles + ⊕ 64+66 *</p> <p>CDE 46 poles + ⊕ 83+85 *</p> <p>CSH 24 poles + ⊕ 91+93 *</p> <p>CCE 24 poles + ⊕ 100+104 *</p> <p>CNE, CSE, JCNE, JCSE 24 poles + ⊕ 101 and 109 *</p> <p>CSS 24 poles + ⊕ 122+123 *</p> <p>CTE, CTSE **) 24 poles + ⊕ 129 *</p> <p>CMSE 10+2 (aux) poles + ⊕ 139 *</p> <p>CMCE 10+2 (aux) poles + ⊕ 138 *</p> <p>CX 4/8 poles + ⊕ 155 *</p> <p>MIXO 6 modules 160+195 *</p> <p>insert centre distance: 104 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p> housings with double lever</p>	<p> hoods with 4 pegs</p>
description	part no. entry	part no. entry
bulkhead mounting housing, with 2 levers	CHIN 24	
surface mounting housing, high construction, with 2 levers	MAPN 24.32 32	
with pegs, side entry		MHON 24.32 32
with pegs, side entry, high construction		MFON 24.32 32
with pegs, side entry		MHVN 24.32 32
with pegs, side entry, high construction		MFVN 24.32 32
**) only in the CHIN 24 enclosure		
<p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>	<p>dimensions in mm</p> <p>CHIN 24</p>	<p>dimensions in mm</p> <p>MFON 24.32</p>
	<p>MAPN 24.32</p>	<p>MFVN 24.32</p>
		<p>MHON 24.32</p>
		<p>MHVN 24.32</p>

dimensions shown are not binding
and may be changed without notice