

Part number

# MHON 16.32



Hood, LS-TYPE series, with 4 pegs, M32 side cable entry, size "77.27"

Product description		Material properties	
Product type	Hood	Colour	RAL 9005 black
Series	LS-TYPE	RoHs conformity	Compliant
Closing type	With 4 pegs	China RoHs - EFUP	E
Size	Size 77.27	REACH SVHC substances	No
Cable entry	Side cable entry M32	Approvals / Standards	
Technical data		Certifications	DNV, BV
IP degree of protection	IP65	UL	ECBT2
Further technical details		cUL	ECBT8
Weight	175,00 g	General ordering information	
Operating temperature range (min, max)	-40°C...+125°C	EAN13 code	8015747194266
		eCl@ss 8.1	27440202
		ETIM 7.0	EC000437
		Packaging Information	
		Sub-packaging weight	0,88 kg
		Sub-packaging description	Plastic packaging
		Sub-packaging quantity	5 Pcs
		Sub-packaging EAN barcode	8015747194273

# Part number MHON 16.32



Catalogue drawings



Catalogue drawings

**CH..N - MA, MF..N enclosures** size "77.27" **LS-TYPE version**

inserts: 

CD	40 poles + @	49+52 *
CT, CTS **)	40 poles + @	56 *
CDD	72 poles + @	62+65 *
CDE	32 poles + @	82+84 *
CSH	16 poles + @	90+92 *
CCE	16 poles + @	98+102 *
CNE, CSE, JCNE, JCSE	16 poles + @	99 and 108 *
CSS	16 poles + @	120+122 *
CTE, CTSE **)	16 poles + @	128 *
CMSE	6+2 (aux) poles + @	137 *
CMCE	6+2 (aux) poles + @	136 *
CP	6 poles + @	149+150 *
CX	6/36 e 12/2 poles + @	152+153 *
CX	4/0 e 4/2 poles + @	154 *
MIXO	4 modules	160-195 *

insert centre distance: 77,5 x 27 mm  
\* refer to catalogue page CN.12

description	part no.		part no.	
	entry	M	entry	M
bulkhead mounting housing, with 2 levers	<b>CHIN 16</b>			
surface mounting housing, high construction, with 2 levers	<b>MAPN 16.32</b>		<b>32</b>	
with pegs, side entry			<b>MHON 16.32</b>	
with pegs, side entry, high construction			<b>MFON 16.32</b>	
with pegs, top entry			<b>MHVN 16.32</b>	
with pegs, top entry, high construction			<b>MFVN 16.32</b>	

\*\*) only in the CHIN 16 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder  
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

**housings with double lever**

**hoods with 4 pegs**

**CHIN 16** dimensions in mm: 130, 58, 29, 103, 115.5, 6, 45.5, 32

**MAPN 16.32** dimensions in mm: 130, 58, 81, 105, 117, 4, 57, 32

**MHON 16.32** dimensions in mm: 93.5, 76, 43, 63

**MFON 16.32** dimensions in mm: 93.5, 76, 43

**MHVN 16.32** dimensions in mm: 93.5, 76, 43, 58