

Part number

# MHON 24.32



Hood, LS-TYPE series, with 4 pegs, M32 side cable entry, size "104.27"

#### Product description

<b>Product type</b>	Hood
<b>Series</b>	LS-TYPE
<b>Closing type</b>	With 4 pegs
<b>Size</b>	Size 104.27
<b>Cable entry</b>	Side cable entry M32

#### Technical data

<b>IP degree of protection</b>	IP65
--------------------------------	------

#### Further technical details

<b>Weight</b>	197,00 g
<b>Operating temperature range (min, max)</b>	-40°C...+125°C

#### Material properties

<b>Colour</b>	RAL 9005 black
<b>RoHs conformity</b>	Compliant
<b>China RoHs - EFUP</b>	E
<b>REACH SVHC substances</b>	No

#### Approvals / Standards

<b>Certifications</b>	DNV, BV
<b>UL</b>	ECBT2
<b>cUL</b>	ECBT8

#### General ordering information

<b>EAN13 code</b>	8015747194303
<b>eCl@ss 8.1</b>	27440202
<b>ETIM 7.0</b>	EC000437

#### Packaging Information

<b>Sub-packaging weight</b>	0,99 kg
<b>Sub-packaging description</b>	Plastic packaging
<b>Sub-packaging quantity</b>	5 Pcs
<b>Sub-packaging EAN barcode</b>	8015747194310

# Part number MHON 24.32



Catalogue drawings



Catalogue drawings

**CH..N - MA, MF..N enclosures**      size "104.27"      LS-TYPE version

<p>inserts: <span style="float: right;">page</span></p> <p>CD ..... 64 poles + ⊕ 51+53 *</p> <p>CT, CTS **) ..... 64 poles + ⊕ 57 *</p> <p>CDD ..... 108 poles + ⊕ 64+66 *</p> <p>CDE ..... 46 poles + ⊕ 83+85 *</p> <p>CSH ..... 24 poles + ⊕ 91+93 *</p> <p>CCE ..... 24 poles + ⊕ 100+104 *</p> <p>CNE, CSE, JCNE, JCSE 24 poles + ⊕ 101 and 109 *</p> <p>CSS ..... 24 poles + ⊕ 122+123 *</p> <p>CTE, CTSE **) ..... 24 poles + ⊕ 129 *</p> <p>CMSE ..... 10+2 (aux) poles + ⊕ 139 *</p> <p>CMCE ..... 10+2 (aux) poles + ⊕ 138 *</p> <p>CX ..... 4/8 poles + ⊕ 155 *</p> <p>MIXO ..... 6 modules 160+195 *</p> <p>insert centre distance: 104 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p><b> housings with double lever</b></p>	<p><b> hoods with 4 pegs</b></p>
description	part no.    entry	part no.    entry
bulkhead mounting housing, with 2 levers	<b>CHIN 24</b>	
surface mounting housing, high construction, with 2 levers	<b>MAPN 24.32</b> <b>32</b>	
with pegs, side entry		<b>MHON 24.32</b> <b>32</b>
with pegs, side entry, high construction		<b>MFON 24.32</b> <b>32</b>
with pegs, side entry		<b>MHVN 24.32</b> <b>32</b>
with pegs, side entry, high construction		<b>MFVN 24.32</b> <b>32</b>
**) only in the CHIN 24 enclosure		
panel cut-out for bulkhead mounting housing in mm	dimensions in mm	dimensions in mm
<p style="font-size: small;">- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>	<p><b>CHIN 24</b></p>	<p><b>MFON 24.32</b></p>
	<p><b>MAPN 24.32</b></p>	<p><b>MFVN 24.32</b></p>
		<p><b>MHON 24.32</b></p>
		<p><b>MHVN 24.32</b></p>
<p style="font-size: x-small;">dimensions shown are not binding and may be changed without notice</p>		