

Part number

# MLFV 24 LG25



Hood, IL-BRID series, with 1 lever, M25 top cable entry without adapter, size "104.27", high construction

| Product description                           |                        | Material properties                 |  |
|---|------------------------|-------------------------------------|--|
| <b>Product type</b>                           | Hood                   | <b>Other materials</b>              | Lever: Polyamide (PA) and Stainless steel core<br>Gasket NBR |
| <b>Series</b>                                 | IL-BRID                | <b>Colour</b>                       | RAL 7040 grey  |
| <b>Closing type</b>                           | With 1 lever           | <b>RoHs conformity</b>              | Compliant  |
| <b>Size</b>                                   | Size 104.27            | <b>China RoHs - EFUP</b>            | E  |
| <b>Cable entry</b>                            | Top cable entry<br>M25 | <b>REACH SVHC substances</b>        | No   |
| <b>Specification</b>                          | High construction      | <b>General ordering information</b> |  |
| <b>Technical data</b>                         |                        | <b>EAN13 code</b>                   | 8015747288439  |
| <b>IP degree of protection</b>                | IP65 / IP66 / IP69     | <b>eCl@ss 8.1</b>                   | 27440202   |
| <b>Further technical details</b>              |                        | <b>ETIM 7.0</b>                     | EC000437   |
| <b>Operating temperature range (min, max)</b> | -40°C...+125°C         | <b>Packaging Information</b>        |  |
|   |                        | <b>Sub-packaging description</b>    | Plastic packaging  |
|   |                        | <b>Sub-packaging quantity</b>       | 5 Pcs  |
|   |                        | <b>Sub-packaging EAN barcode</b>    | 8015747294515  |

Part number

# MLFV 24 LG25



## Catalogue drawings

