

Part number

PE 1663 SV



Mobile plug, PLUSO series, 2 poles + PE, 6 h (blue), 16 A, 200 ÷ 250 V, straight

Product description		Material properties	
Product type	Plug Mobile	Colour	RAL 7035 grey, RAL 5015 blue
Series	PE...SV, PLUSO	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Connection type	Screw terminal connection	China RoHs - EFUP	50
N. of poles	2 poles + 	REACH SVHC substances	Yes Lead
Clock position	6	SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade
Specification	Straight	Approvals / Standards	
Technical data		Reference standard	EN 60309-1 and -2
Current	16 A	General ordering information	
Voltage	200 ÷ 250 V	EAN13 code	8015747064538
IP degree of protection	IP44	Packaging Information	
Further technical details		Packaging length	400,00 mm
Weight	100,00 g	Packaging height	300,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Packaging width	400,00 mm
		Packaging weight	10,27 kg
		Packaging volume	48,00 dm³
		Packaging description	Carton box
		Packaging quantity	100 Pcs
		Packaging EAN code	8015747064545


Part number

PE 1663 SV



Catalogue drawings

(16 / 32A) PE ... SV



PE...SV	A	B	ø min	ø max
16A 2P+⊕	129	59,5	7	16
3P+⊕	129	67	7	16
3P+N+⊕	129	75	8	24
32A 2P+⊕	150	81	8	24
3P+⊕	150	81	8	24
3P+N+⊕	150	90	8	24