


Part number

PE 1673 SV



Mobile plug, PLUSO series, 2 poles + PE, 7 h (black), 16 A, 480 ÷ 500 V, straight

Product description		Material properties	
Product type	Plug Mobile	Colour	RAL 7035 grey, RAL 9005 black
Series	PE...SV, PLUSO	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Connection type	Screw terminal connection	China RoHs - EFUP	50
N. of poles	2 poles + 	REACH SVHC substances	Yes Lead
Clock position	7	SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade
Specification	Straight	Approvals / Standards	
Technical data		Reference standard	EN 60309-1 and -2
Current	16 A	General ordering information	
Voltage	480 ÷ 500 V	EAN13 code	8015747064910
IP degree of protection	IP44	Packaging Information	
Further technical details		Sub-packaging length	162,00 mm
Weight	100,00 g	Sub-packaging height	87,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Sub-packaging width	233,00 mm
		Sub-packaging weight	1,00 kg
		Sub-packaging volume	3,28 dm ³
		Sub-packaging description	Carton box
		Sub-packaging quantity	10 Pcs
		Sub-packaging EAN barcode	8015747064927

Part number

PE 1673 SV



Catalogue drawings

(16 / 32A) PE ... SV



PE ... SV	A	B	Ø min	Ø max	
16A 2P+⊕	143,5	59	7	17	
	3P+⊕	148,5	66	7	17
	3P+N+⊕	167,5	75	9	22
32A 2P+⊕	187	80	9	22	
	3P+⊕	187	80	9	22
	3P+N+⊕	192,5	87	9	22