


Part number

PE 1693 PV



Mobile socket outlet, PLUSO series, 2 poles + PE, 9 h (red), 16 A, 380 ÷ 415 V

Product description		Material properties	
Product type	Socket Mobile	Colour	RAL 7035 grey, RAL 3000 red
Series	PE...PV, PLUSO	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Connection type	Screw terminal connection	China RoHs - EFUP	50
N. of poles	2 poles + 	REACH SVHC substances	Yes Lead
Clock position	9	SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade
Technical data		Approvals / Standards	
Current	16 A	Reference standard	EN 60309-1 and -2
Voltage	380 ÷ 415 V	General ordering information	
IP degree of protection	IP44	EAN13 code	8015747065399
Further technical details		Packaging Information	
Weight	131,00 g	Packaging length	208,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Packaging height	140,00 mm
		Packaging width	290,00 mm
		Sub-packaging weight	1,31 kg
		Sub-packaging description	Carton box
		Sub-packaging quantity	10 Pcs
		Sub-packaging EAN barcode	8015747065405

Part number

PE 1693 PV



Catalogue drawings

(16 / 32A) PE ... PV



PE...PV	A	B	\varnothing min	\varnothing max	
16A 2P+ \oplus	157,5	68	7	17	
	3P+ \oplus	164,5	76	7	17
	3P+N+ \oplus	183,5	83	9	22
32A 2P+ \oplus	200,5	87	9	22	
	3P+ \oplus	200,5	87	9	22
	3P+N+ \oplus	200,5	91	9	22