


Part number

PE 1694 PV



Mobile socket outlet, PLUSO series, 3 poles + PE, 9 h (blue), 16 A, 200 ÷ 250 V

Product description

Product type	Socket Mobile
Series	PE...PV, PLUSO
Connection type	Screw terminal connection
N. of poles	3 poles + 
Clock position	9

Technical data

Current	16 A
Voltage	200 ÷ 250 V
IP degree of protection	IP44

Further technical details

Weight	155,50 g
Operating temperature range (min, max)	-25°C ... +40°C

Material properties

Colour	RAL 7035 grey, RAL 5015 blue
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade

Approvals / Standards

Reference standard	EN 60309-1 and -2
---------------------------	-------------------

General ordering information

EAN13 code	8015747065597
-------------------	---------------

Packaging Information

Packaging length	208,00 mm
Packaging height	140,00 mm
Packaging width	290,00 mm
Packaging weight	1,78 kg
Packaging volume	8,44 dm ³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747217323


Part number

PE 1694 PV



Catalogue drawings

(16 / 32A) PE ... PV



PE...PV	A	B	Ø min	Ø max
16A 2P+⊕	157,5	68	7	17
3P+⊕	164,5	76	7	17
3P+N+⊕	183,5	83	9	22
32A 2P+⊕	200,5	87	9	22
3P+⊕	200,5	87	9	22
3P+N+⊕	200,5	91	9	22