


Part number

# PE 3233 PV



Mobile socket outlet, PLUSO series, 2 poles + PE, 3 h (white), 32 A, 50 ÷ 250 V

| Product description                           |   | Material properties          |   |
|---|---|------------------------------|---|
| <b>Product type</b>                           | Socket<br>Mobile  | <b>Colour</b>                | RAL 7035 grey, RAL 9010 white   |
| <b>Series</b>                                 | PE...PV, PLUSO  | <b>RoHs conformity</b>       | Compliant with exemption<br>6(c): copper alloy containing up to 4% lead by weight |
| <b>N. of poles</b>                            | 2 poles +  | <b>China RoHs - EFUP</b>     | 50  |
| <b>Clock position</b>                         | 3   | <b>REACH SVHC substances</b> | Yes<br>Lead   |
| Technical data                                |   | <b>SCIP number</b>           | Ca7de37f-add8-4b77-9861-279c94903ade  |
| <b>Current</b>                                | 32 A  | Approvals / Standards        |   |
| <b>Voltage</b>                                | > 50 ÷ 250 V  | <b>Reference standard</b>    | EN 60309-1 and -2   |
| <b>IP degree of protection</b>                | IP44  | General ordering information |   |
| Further technical details                     |   | <b>EAN13 code</b>            | 8015747066488   |
| <b>Weight</b>                                 | 230,00 g  | Packaging Information        |   |
| <b>Operating temperature range (min, max)</b> | -25°C ... +40°C   | <b>Packaging length</b>      | 285,00 mm   |
|   |   | <b>Packaging height</b>      | 170,00 mm   |
|   |   | <b>Packaging width</b>       | 190,00 mm   |
|   |   | <b>Packaging weight</b>      | 2,45 kg   |
|   |   | <b>Packaging volume</b>      | 9,21 dm <sup>3</sup>  |
|   |   | <b>Packaging description</b> | Carton box  |
|   |   | <b>Packaging quantity</b>    | 10 Pcs  |
|   |   | <b>Packaging EAN code</b>    | 8015747066495   |

Part number

# PE 3233 PV



Catalogue drawings

(16 / 32A) PE ... PV



| PE...PV    |        | A     | B  | Ø min | Ø max |
|------------|--------|-------|----|-------|-------|
| <b>16A</b> | 2P+⊕   | 157,5 | 68 | 7     | 17    |
|            | 3P+⊕   | 164,5 | 76 | 7     | 17    |
|            | 3P+N+⊕ | 183,5 | 83 | 9     | 22    |
| <b>32A</b> | 2P+⊕   | 200,5 | 87 | 9     | 22    |
|            | 3P+⊕   | 200,5 | 87 | 9     | 22    |
|            | 3P+N+⊕ | 200,5 | 91 | 9     | 22    |