


Part number

# PEW 1633 SI



Flush-mounting plug, PLUSO series, 2 poles + PE, 3 h (white), 16 A, 50 ÷ 250 V

#### Product description

|                       |                                                                                             |
|-----------------------|---------------------------------------------------------------------------------------------|
| <b>Product type</b>   | Plug<br>Flush-mounting                                                                      |
| <b>Series</b>         | PEW...SI, PLUSO                                                                             |
| <b>N. of poles</b>    | 2 poles +  |
| <b>Clock position</b> | 3                                                                                           |

#### Technical data

|                                |              |
|--------------------------------|--------------|
| <b>Current</b>                 | 16 A         |
| <b>Voltage</b>                 | > 50 ÷ 250 V |
| <b>IP degree of protection</b> | IP67         |

#### Further technical details

|                                               |                 |
|-----------------------------------------------|-----------------|
| <b>Operating temperature range (min, max)</b> | -25°C ... +40°C |
|-----------------------------------------------|-----------------|

#### Material properties

|               |                               |
|---------------|-------------------------------|
| <b>Colour</b> | RAL 7035 grey, RAL 9010 white |
|---------------|-------------------------------|

#### Approvals / Standards

|                           |                   |
|---------------------------|-------------------|
| <b>Reference standard</b> | EN 60309-1 and -2 |
|---------------------------|-------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747156929 |
|-------------------|---------------|

Part number

# PEW 1633 SI



Catalogue drawings

(16 / 32A) PEW ... SI



| PEW ... SI      | A  | B   | C   | D   | E  | F  | G    | H   | X  | Y  |
|-----------------|----|-----|-----|-----|----|----|------|-----|----|----|
| <b>16A</b> 2P+⊕ | 65 | 82  | 126 | 81  | 41 | 43 | 21,5 | 70  | 52 | 60 |
| 3P+⊕            | 65 | 82  | 126 | 81  | 47 | 43 | 24,5 | 78  | 52 | 60 |
| 3P+N+⊕          | 90 | 100 | 146 | 93  | 54 | 60 | 27,5 | 86  | 77 | 85 |
| <b>32A</b> 2P+⊕ | 90 | 100 | 160 | 101 | 55 | 60 | 27,5 | 92  | 77 | 85 |
| 3P+⊕            | 90 | 100 | 160 | 101 | 55 | 60 | 27,5 | 92  | 77 | 85 |
| 3P+N+⊕          | 90 | 100 | 160 | 101 | 62 | 60 | 27,5 | 100 | 77 | 85 |