

Part number

# PK 12565 PB5



Interlocked switched socket-outlet, PK series,  
3 poles + N + PE, 6 h (red), 125 A, 346 ÷ 415  
V, NH00 fuse carrier

| Product description                            |                                    |
|--|------------------------------------|
| <b>Product type</b>                            | Interlocked switched socket-outlet |
| <b>Series</b>                                  | PK..PB5                            |
| <b>N. of poles</b>                             | 3 poles + N +                      |
| <b>Clock position</b>                          | 6                                  |
| <b>Specification</b>                           | NH00 fuse carrier                  |
| Technical data                                 |                                    |
| <b>Current</b>                                 | 125 A                              |
| <b>Voltage</b>                                 | 346 - 415 V                        |
| <b>IP degree of protection</b>                 | IP55                               |
| Further technical details                      |                                    |
| <b>Weight</b>                                  | 9.200,00 g                         |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C                    |
| <b>IK rating (impact degree of protection)</b> | IK10                               |

| Material properties          |  |
|------------------------------|--|
| <b>Colour</b>                | RAL 7035 grey, RAL 3000 red  |
| <b>RoHs conformity</b>       | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| <b>China RoHs - EFUP</b>     | 50   |
| <b>REACH SVHC substances</b> | Yes<br>Lead  |
| <b>SCIP number</b>           | Ce861c8d-b979-403b-96d9-80aef6dc281d   |
| Approvals / Standards        |  |
| <b>Reference standard</b>    | EN 60309-1, -2 e -4  |
| General ordering information |  |
| <b>EAN13 code</b>            | 8015747079426  |
| Packaging Information        |  |
| <b>Packaging length</b>      | 570,00 mm  |
| <b>Packaging height</b>      | 200,00 mm  |
| <b>Packaging width</b>       | 265,00 mm  |
| <b>Packaging weight</b>      | 9,90 kg  |
| <b>Packaging volume</b>      | 30,21 dm <sup>3</sup>  |
| <b>Packaging description</b> | Carton box   |
| <b>Packaging quantity</b>    | 1 Pcs  |
| <b>Packaging EAN code</b>    | 8015747079433  |
| <b>Sub-packaging length</b>  | 113,00 mm  |
| <b>Sub-packaging height</b>  | 36,00 mm   |
| <b>Sub-packaging width</b>   | 180,00 mm  |
| <b>Sub-packaging volume</b>  | 0,73 dm <sup>3</sup>   |

Part number

# PK 12565 PB5



## Catalogue drawings

