

Part number

PK 3264 PB5



Interlocked switched socket-outlet, PK series,
3 poles + PE, 6 h (red), 32 A, 380 ÷ 415 V,
E33 - DIII fuse carrier

Product description

Product type	Interlocked switched socket-outlet
Series	PK..PB5
N. of poles	3 poles +
Clock position	6
Specification	E33 - DIII fuse carrier

Technical data

Current	32 A
Voltage	380 ÷ 415 V
IP degree of protection	IP55

Further technical details

Weight	3.300,00 g
Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7035 grey, RAL 3000 red
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	F6799547-ab84-42f2-938f-233ba663766d

Approvals / Standards

Reference standard	EN 60309-1, -2 e -4
---------------------------	---------------------

General ordering information

EAN13 code	8015747081481
-------------------	---------------

Packaging Information



Sub-packaging length	150,00 mm
Sub-packaging height	140,00 mm
Sub-packaging width	380,00 mm
Sub-packaging weight	3,30 kg
Sub-packaging volume	7,98 dm ³
Sub-packaging description	Carton box
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747081504

Part number

PK 3264 PB5



Catalogue drawings



	A
2P+⊕	363
3P+⊕	370
3P+N+⊕	370