

Part number

PK 63114 PB5



Interlocked switched socket-outlet, PK series,
3 poles + PE, 11 h (red), 63 A, 440 ÷ 460 V,
E33 - DIII fuse carrier

Product description	
Product type	Interlocked switched socket-outlet
Series	PK..PB5
N. of poles	3 poles +
Clock position	11
Specification	E33 - DIII fuse carrier
Technical data	
Current	63 A
Voltage	440 ÷ 460 V
IP degree of protection	IP55
Further technical details	
Weight	3.600,00 g
Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10


Material properties	
Colour	RAL 7035 grey, RAL 3000 red
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4
General ordering information	
EAN13 code	8015747082150
Packaging Information	
Packaging length	400,00 mm
Packaging height	165,00 mm
Packaging width	170,00 mm
Packaging weight	4,10 kg
Packaging volume	11,22 dm ³
Packaging description	Carton box
Packaging quantity	1 Pcs
Packaging EAN code	8015747082167

Part number

PK 63114 PB5



Catalogue drawings



	A
2P+⊕	360
3P+⊕	360
3P+N+⊕	382