


Part number

SQV 1644.5



Interlocked switched socket-outlet, SQV series, 3 poles + PE, 4 h (yellow), 16 A, 100 ÷ 130 V, sectionable fuse carrier 10 x 38 mm

| Product description | | Material properties | |
|--|---|----------------------------------|--|
| Product type | Interlocked switched socket-outlet | Colour | RAL 7035 grey, RAL 1021 yellow |
| Series | SQV | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 3 poles +  | RoHs conformity | 6(c): copper alloy containing up to 4% lead by weight |
| Clock position | 4 | China RoHs - EFUP | 50 |
| Size | Socket fixing centre distance 88 x 230 mm | REACH SVHC substances | Yes Lead |
| Specification | Sectionable fuse carrier 10 x 38 mm | SCIP number | F6799547-ab84-42f2-938f-233ba663766d |
| Technical data | | Approvals / Standards | |
| Current | 16 A | Reference standard | EN 60309-1, -2 e -4 |
| Voltage | 100 ÷ 130 V | General ordering information | |
| IP degree of protection | IP55 | EAN13 code | 8015747087483 |
| Further technical details | | Packaging Information | |
| Weight | 650,00 g | Sub-packaging length | 116,00 mm |
| Operating temperature range (min, max) | -25°C ... +40°C | Sub-packaging height | 103,00 mm |
| IK rating (impact degree of protection) | IK08 | Sub-packaging width | 230,00 mm |
| | | Sub-packaging weight | 0,65 kg |
| | | Sub-packaging volume | 2,75 dm ³ |
| | | Sub-packaging description | Carton box |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747087490 |

Part number

SQV 1644.5



Catalogue drawings



Catalogue drawings



| SQV.5 | | A |
|-------|--------|----|
| 16A | 2P+⊕ | 67 |
| | 3P+⊕ | 67 |
| | 3P+N+⊕ | 70 |