


Part number

TM 16104 SSP



Interlocked switched socket-outlet, TM series,
3 poles + PE, 10 h (green), 16 A, > 50 V,
without fuse-carrier, without base box

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM..SSP/KSSP |
| N. of poles | 3 poles +  |
| Clock position | 10 |
| Specification | Without fuse-carrier Without base box |

Technical data

| | |
|--------------------------------|-------------|
| Current | 16 A |
| Voltage | > 50 V |
| IP degree of protection | IP66 / IP67 |

Further technical details

| | |
|--|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|---------------|-------------------------------|
| Colour | RAL 7012 grey, RAL 6017 green |
|---------------|-------------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747160575 |
|-------------------|---------------|

Part number

TM 16104 SSP



Catalogue drawings



| | A | B |
|---------------|----------|----------|
| 2P+⊕ | 83 | 276 |
| 3P+⊕ | 85 | 276 |
| 3P+N+⊕ | 90 | 277 |