


Part number

# TM 1643 IS



Interlocked switched socket-outlet, TM series, 2 poles + PE, 4 h (yellow), 16 A, 100 ÷ 130 V, sectionable fuse carrier 10 x 38 mm, with base box

| Product description                            |   | Material properties              |  |
|--|---|----------------------------------|--|
| <b>Product type</b>                            | Interlocked switched socket-outlet  | <b>Colour</b>                    | RAL 7012 grey, RAL 1021 yellow   |
| <b>Series</b>                                  | TM.. IS/KIS   |                                  | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| <b>N. of poles</b>                             | 2 poles +  | <b>RoHs conformity</b>           | 6(c): copper alloy containing up to 4% lead by weight                          |
| <b>Clock position</b>                          | 4   | <b>China RoHs - EFUP</b>         | 50   |
| <b>Size</b>                                    | 115 x 450 x 18 mm   | <b>REACH SVHC substances</b>     | Yes<br>Lead  |
| <b>Specification</b>                           | Sectionable fuse carrier 10 x 38 mm<br>With base box  | <b>SCIP number</b>               | Ce861c8d-b979-403b-96d9-80aef6dc281d   |
| Technical data                                 |   | Approvals / Standards            |  |
| <b>Current</b>                                 | 16 A  | <b>Reference standard</b>        | EN 60309-1, -2 e -4  |
| <b>Voltage</b>                                 | 100 ÷ 130 V   | General ordering information     |  |
| <b>IP degree of protection</b>                 | IP66 / IP67   | <b>EAN13 code</b>                | 8015747089562  |
| Further technical details                      |   | Packaging Information            |  |
| <b>Weight</b>                                  | 1.490,00 g  | <b>Packaging weight</b>          | 13,96 kg   |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C   | <b>Packaging volume</b>          | 52,36 dm <sup>3</sup>  |
| <b>UL 94 flammability rating</b>               | V-2   | <b>Packaging description</b>     | Carton box   |
| <b>IK rating (impact degree of protection)</b> | IK10  | <b>Packaging quantity</b>        | 9 Pcs  |
|  |   | <b>Packaging EAN code</b>        | 8015747220323  |
|  |   | <b>Sub-packaging weight</b>      | 1,55 kg  |
|  |   | <b>Sub-packaging description</b> | Plastic packaging  |
|  |   | <b>Sub-packaging quantity</b>    | 1 Pcs  |
|  |   | <b>Sub-packaging EAN barcode</b> | 8015747106955  |

Part number

# TM 1643 IS



Catalogue drawings



|                | A   | B   |
|----------------|-----|-----|
| 2P+ $\oplus$   | 133 | 276 |
| 3P+ $\oplus$   | 135 | 276 |
| 3P+N+ $\oplus$ | 140 | 277 |