


Part number

TM 1674 SSP



Interlocked switched socket-outlet, TM series, 3 poles + PE, 7 h (black), 16 A, 480 ÷ 500 V, without fuse-carrier, without base box

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7012 grey, RAL 9005 black
Series	TM..SSP/KSSP		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + 	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Clock position	7	China RoHs - EFUP	50
Specification	Without fuse-carrier Without base box	REACH SVHC substances	Yes Lead
Technical data		SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d
Current	16 A	Approvals / Standards	
Voltage	480 ÷ 500 V	Reference standard	EN 60309-1, -2 e -4
IP degree of protection	IP66 / IP67	General ordering information	
Further technical details		EAN13 code	8015747100953
Weight	1.045,00 g	Packaging Information	
Operating temperature range (min, max)	-25°C ... +40°C	Packaging weight	10,00 kg
UL 94 flammability rating	V-2	Packaging volume	52,36 dm ³
IK rating (impact degree of protection)	IK10	Packaging description	Carton box
		Packaging quantity	9 Pcs
		Packaging EAN code	8015747035729
		Sub-packaging length	95,00 mm
		Sub-packaging height	40,00 mm
		Sub-packaging width	253,00 mm
		Sub-packaging weight	1,11 kg
		Sub-packaging volume	0,96 dm ³
		Sub-packaging description	Plastic packaging
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747083461

Part number

TM 1674 SSP



Catalogue drawings



	A	B
2P+⊕	83	276
3P+⊕	85	276
3P+N+⊕	90	277