

Part number

TM 1693 IR



Interlocked switched socket-outlet, TM series, 2 poles + PE, 9 h (red), 16 A, 380 ÷ 415 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, with base box

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7012 grey, RAL 3000 red
Series	TM..IR/KIR		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	2 poles +	RoHs conformity	50
Clock position	9	China RoHs - EFUP	50
Size	115 x 450 x 18 mm	REACH SVHC substances	Yes Lead
Specification	With compartment for modular units, 4,5 DIN-rail modules EN 60715 With base box	SCIP number	Ce861c8d-b979-403b-96d9-80aef6dc281d
Technical data		Approvals / Standards	
Current	16 A	Reference standard	EN 60309-1, -2 e -4
Voltage	380 ÷ 415 V	General ordering information	
IP degree of protection	IP66 / IP67	EAN13 code	8015747090414
Further technical details		Packaging Information	
Weight	1.310,00 g	Sub-packaging length	287,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Sub-packaging height	140,00 mm
UL 94 flammability rating	V-2	Sub-packaging width	125,00 mm
IK rating (impact degree of protection)	IK10	Sub-packaging weight	1,31 kg
		Sub-packaging volume	5,02 dm ³
		Sub-packaging description	Carton box
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747098717

Part number

TM 1693 IR



Catalogue drawings



	A	B
2P+ \oplus	133	276
3P+ \oplus	135	276
3P+N+ \oplus	140	277