


Part number

TM 1695 IT



Interlocked switched socket-outlet, TM series,
3 poles + N + PE, 9 h (blue), 16 A, 120/208 ÷
144/250 V, E16 fuse carrier, with base box

| Product description | |
|--|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM.. IT |
| N. of poles | 3 poles + N +  |
| Clock position | 9 |
| Size | 115 x 450 x 18 mm |
| Specification | E16 fuse carrier With base box |
| Technical data | |
| Current | 16 A |
| Voltage | 120/208 ÷ 144/250 V |
| IP degree of protection | IP66 / IP67 |
| Further technical details | |
| Weight | 1.630,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

| Material properties | |
|----------------------------------|------------------------------|
| Colour | RAL 7012 grey, RAL 5015 blue |
| Approvals / Standards | |
| Reference standard | EN 60309-1, -2 e -4 |
| General ordering information | |
| EAN13 code | 8015747090575 |
| Packaging Information | |
| Sub-packaging weight | 1,63 kg |
| Sub-packaging description | Plastic packaging |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747107143 |

Part number

TM 1695 IT



Catalogue drawings



| | A | B |
|----------------|-----|-----|
| 2P+ \oplus | 133 | 276 |
| 3P+ \oplus | 135 | 276 |
| 3P+N+ \oplus | 140 | 277 |