


Part number

TM 3263KIR



Interlocked switched socket-outlet, TM series, 2 poles + PE, 6 h (blue), 32 A, 200 ÷ 250 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, with base box

| Product description | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM..IR/KIR |
| N. of poles | 2 poles +  |
| Clock position | 6 |
| Size | 115 x 450 x 18 mm |
| Specification | With compartment for modular units, 4,5 DIN-rail modules EN 60715 With base box |

| Technical data | |
|--------------------------------|-------------|
| Current | 32 A |
| Voltage | 200 ÷ 250 V |
| IP degree of protection | IP66 / IP67 |

| Further technical details | |
|--|-----------------|
| Weight | 1.370,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

| Material properties | |
|------------------------------|--|
| Colour | RAL 7012 grey, RAL 5015 blue |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |

| Approvals / Standards | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |

| General ordering information | |
|------------------------------|---------------|
| EAN13 code | 8015747126014 |

| Packaging Information | |
|----------------------------------|-----------------------|
| Packaging weight | 12,33 kg |
| Packaging volume | 55,44 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 9 Pcs |
| Packaging EAN code | 8015747126762 |
| Sub-packaging weight | 1,37 kg |
| Sub-packaging description | Carton tray |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747126779 |

Part number

TM 3263KIR



Catalogue drawings



| | A | B |
|--------|-----|-----|
| 2P+⊕ | 133 | 276 |
| 3P+⊕ | 135 | 276 |
| 3P+N+⊕ | 140 | 277 |