


Part number

TM 3263KSIR



Interlocked switched socket-outlet, TM series, 2 poles + PE, 6 h (blue), 32 A, 200 ÷ 250 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, without base box

| Product description | |
|--|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM..SIR/KSIR |
| N. of poles | 2 poles +  |
| Clock position | 6 |
| Size | 114 x 255 mm fixing distance, for assembly in single or multiple boxes |
| Specification | With compartment for modular units, 4,5 DIN-rail modules EN 60715 Without base box |
| Technical data | |
| Current | 32 A |
| Voltage | 200 ÷ 250 V |
| IP degree of protection | IP66 / IP67 |
| Further technical details | |
| Weight | 1.000,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

| Material properties | |
|----------------------------------|--|
| Colour | RAL 7012 grey, RAL 5015 blue |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |
| Approvals / Standards | |
| Reference standard | EN 60309-1, -2 e -4 |
| General ordering information | |
| EAN13 code | 8015747126021 |
| Packaging Information | |
| Packaging length | 385,00 mm |
| Packaging height | 320,00 mm |
| Packaging width | 485,00 mm |
| Packaging weight | 9,40 kg |
| Packaging volume | 59,75 dm ³ |
| Packaging description | Plastic packaging |
| Packaging quantity | 9 Pcs |
| Packaging EAN code | 8015747126625 |
| Sub-packaging length | 95,00 mm |
| Sub-packaging height | 40,00 mm |
| Sub-packaging width | 253,00 mm |
| Sub-packaging weight | 1,04 kg |
| Sub-packaging volume | 0,96 dm ³ |
| Sub-packaging description | Carton tray |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747126632 |

Part number

TM 3263KSIR



Catalogue drawings



| | A |
|---------------|----------|
| 2P+⊕ | 96 |
| 3P+⊕ | 96 |
| 3P+N+⊕ | 101 |