


Part number

# TM 3264 SP



Interlocked switched socket-outlet, TM series,  
3 poles + PE, 6 h (red), 32 A, 380 ÷ 415 V,  
without fuse-carrier, with base box

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Interlocked switched socket-outlet  |
| <b>Series</b>         | TM..SP/KSP  |
| <b>N. of poles</b>    | 3 poles +  |
| <b>Clock position</b> | 6   |
| <b>Size</b>           | 145 x 565 x 18 mm   |
| <b>Specification</b>  | Without fuse-carrier<br>With base box   |

#### Technical data

|                                |             |
|--------------------------------|-------------|
| <b>Current</b>                 | 32 A        |
| <b>Voltage</b>                 | 380 ÷ 415 V |
| <b>IP degree of protection</b> | IP66 / IP67 |

#### Further technical details

|  |                 |
|--|-----------------|
| <b>Weight</b>                                  | 2.895,00 g      |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C |
| <b>UL 94 flammability rating</b>               | V-2             |
| <b>IK rating (impact degree of protection)</b> | IK10            |

#### Material properties

|                              |   |
|------------------------------|---|
| <b>Colour</b>                | RAL 7012 grey, RAL 3000 red   |
| <b>RoHs conformity</b>       | Compliant with exemption<br>6(c): copper alloy containing up to 4% lead by weight |
| <b>China RoHs - EFUP</b>     | 50  |
| <b>REACH SVHC substances</b> | Yes<br>Lead   |
| <b>SCIP number</b>           | F6799547-ab84-42f2-938f-233ba663766d  |

#### Approvals / Standards

|                           |                     |
|---------------------------|---------------------|
| <b>Reference standard</b> | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747100533 |
|-------------------|---------------|

#### Packaging Information

|                                  |                       |
|----------------------------------|-----------------------|
| <b>Sub-packaging length</b>      | 150,00 mm             |
| <b>Sub-packaging height</b>      | 188,00 mm             |
| <b>Sub-packaging width</b>       | 430,00 mm             |
| <b>Sub-packaging weight</b>      | 2,90 kg               |
| <b>Sub-packaging volume</b>      | 12,13 dm <sup>3</sup> |
| <b>Sub-packaging description</b> | Carton box            |
| <b>Sub-packaging quantity</b>    | 1 Pcs                 |
| <b>Sub-packaging EAN barcode</b> | 8015747103053         |

Part number

# TM 3264 SP



Catalogue drawings



|               | <b>A</b> |
|---------------|----------|
| <b>2P+⊕</b>   | 162      |
| <b>3P+⊕</b>   | 162      |
| <b>3P+N+⊕</b> | 169      |