


Part number

TM 3264 SSP



Interlocked switched socket-outlet, TM series,
3 poles + PE, 6 h (red), 32 A, 380 ÷ 415 V,
without fuse-carrier, without base box

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM..SSP/KSSP |
| N. of poles | 3 poles +  |
| Clock position | 6 |
| Size | 144 x 370 mm fixing distance, for assembly in single boxes |
| Specification | Without fuse-carrier Without base box |

Technical data

| | |
|--------------------------------|-------------|
| Current | 32 A |
| Voltage | 380 ÷ 415 V |
| IP degree of protection | IP66 / IP67 |

Further technical details

| | |
|--|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7012 grey, RAL 3000 red |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | F6799547-ab84-42f2-938f-233ba663766d |

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747214766 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|-----------------------|
| Sub-packaging length | 150,00 mm |
| Sub-packaging height | 188,00 mm |
| Sub-packaging width | 430,00 mm |
| Sub-packaging volume | 12,13 dm ³ |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747011501 |