


Part number

# TM 6343 IS



Interlocked switched socket-outlet, TM series, 2 poles + PE, 4 h (yellow), 63 A, 100 ÷ 130 V, sectionable fuse carrier 22 x 58 mm, with base box

| Product description                            |   |
|--|---|
| <b>Product type</b>                            | Interlocked switched socket-outlet  |
| <b>Series</b>                                  | TM.. IS/KIS   |
| <b>N. of poles</b>                             | 2 poles +  |
| <b>Clock position</b>                          | 4   |
| <b>Size</b>                                    | 145 x 565 x 18 mm   |
| <b>Specification</b>                           | Sectionable fuse carrier 22 x 58 mm<br>With base box  |
| Technical data                                 |   |
| <b>Current</b>                                 | 63 A  |
| <b>Voltage</b>                                 | 100 ÷ 130 V   |
| <b>IP degree of protection</b>                 | IP66 / IP67   |
| Further technical details                      |   |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C   |
| <b>UL 94 flammability rating</b>               | V-0 (insert), V-2 (enclosure)   |
| <b>IK rating (impact degree of protection)</b> | IK10  |

| Material properties              |                                |
|----------------------------------|--------------------------------|
| <b>Colour</b>                    | RAL 7012 grey, RAL 1021 yellow |
| Approvals / Standards            |                                |
| <b>Reference standard</b>        | EN 60309-1, -2 e -4            |
| General ordering information     |                                |
| <b>EAN13 code</b>                | 8015747092371                  |
| Packaging Information            |                                |
| <b>Sub-packaging description</b> | Carton box                     |
| <b>Sub-packaging quantity</b>    | 1 Pcs                          |
| <b>Sub-packaging EAN barcode</b> | 8015747108805                  |

Part number

# TM 6343 IS



Catalogue drawings

