


Part number

TM 6364 IR



Interlocked switched socket-outlet, TM series, 3 poles + PE, 6 h (red), 63 A, 380 ÷ 415 V, with compartment for modular units, 6 DIN-rail modules EN 60715, with base box

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM..IR/KIR |
| N. of poles | 3 poles +  |
| Clock position | 6 |
| Size | 145 x 565 x 18 mm |
| Specification | With compartment for modular units, 6 DIN-rail modules EN 60715 With base box |

Technical data

| | |
|--|-------------------------------|
| Current | 63 A |
| Voltage | 380 ÷ 415 V |
| IP degree of protection | IP66 / IP67 |
| Further technical details | |
| Weight | 3.410,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-0 (insert), V-2 (enclosure) |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7012 grey, RAL 3000 red |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | F6799547-ab84-42f2-938f-233ba663766d |

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747092548 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|-----------------------|
| Sub-packaging length | 150,00 mm |
| Sub-packaging height | 188,00 mm |
| Sub-packaging width | 430,00 mm |
| Sub-packaging weight | 3,41 kg |
| Sub-packaging volume | 12,13 dm ³ |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747092562 |

Part number

TM 6364 IR



Catalogue drawings

