


Part number

TM 6364 SIR



Interlocked switched socket-outlet, TM series, 3 poles + PE, 6 h (red), 63 A, 380 ÷ 415 V, with compartment for modular units, 6 DIN-rail modules EN 60715, without base box

Product description	
Product type	Interlocked switched socket-outlet
Series	TM..SIR/KSIR
N. of poles	3 poles + 
Clock position	6
Size	144 x 370 mm fixing distance, for assembly in single boxes
Specification	With compartment for modular units, 6 DIN-rail modules EN 60715 Without base box
Technical data	
Current	63 A
Voltage	380 ÷ 415 V
IP degree of protection	IP66 / IP67
Further technical details	
Weight	2.620,00 g
Operating temperature range (min, max)	-25°C ... +40°C
UL 94 flammability rating	V-0 (insert), V-2 (enclosure)
IK rating (impact degree of protection)	IK10

Material properties	
Colour	RAL 7012 grey, RAL 3000 red
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Approvals / Standards	
Reference standard	EN 60309-1, -2 e -4
General ordering information	
EAN13 code	8015747214827
Packaging Information	
Sub-packaging length	150,00 mm
Sub-packaging height	188,00 mm
Sub-packaging width	430,00 mm
Sub-packaging weight	2,62 kg
Sub-packaging volume	12,13 dm ³
Sub-packaging description	Carton box
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747012096