

Part number

# CAF 50.21



Hood, C-TYPE series, with 4 pegs, Pg21 frontal cable entry, size "66.40", high construction

| Product description                           |                                       |
|---|---------------------------------------|
| <b>Product type</b>                           | Hood                                  |
| <b>Series</b>                                 | C-TYPE                                |
| <b>Closing type</b>                           | With 4 pegs                           |
| <b>Size</b>                                   | Size "66.40"                          |
| <b>Cable entry</b>                            | Frontal cable entry with adapter Pg21 |
| <b>Specification</b>                          | High construction                     |
| Technical data                                |                                       |
| <b>IP degree of protection</b>                | IP65 / IP66 / IP69                    |
| Further technical details                     |                                       |
| <b>Operating temperature range (min, max)</b> | -40°C...+125°C                        |

| Material properties              |  |
|----------------------------------|--|
| <b>Colour</b>                    | RAL 7040 grey  |
| <b>RoHs conformity</b>           | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| <b>China RoHs - EFUP</b>         | 50   |
| <b>REACH SVHC substances</b>     | Yes<br>Lead  |
| <b>SCIP number</b>               | 15deaf78-e939-4401-a0b0-e2228ca32a03   |
| Approvals / Standards            |  |
| <b>Certifications</b>            | DNV, BV  |
| <b>UL</b>                        | ECBT2  |
| <b>cUL</b>                       | ECBT8  |
| General ordering information     |  |
| <b>EAN13 code</b>                | 8015747006026  |
| Packaging Information            |  |
| <b>Sub-packaging description</b> | Carton box   |
| <b>Sub-packaging quantity</b>    | 5 Pcs  |
| <b>Sub-packaging EAN barcode</b> | 8015747199254  |