

Part number

CDMD 0.5



Male crimp contact, CD series, 10 A, turned gold plated, wire cross section 0,5 mm², AWG 20


Product description		Material properties	
Product type	Crimp contact	Main material	Copper alloy
Series	CD		Compliant with exemption
Gender	Male	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Technical data		China RoHs - EFUP	50
Current	10 A	REACH SVHC substances	Yes
Wire cross-section	0,50 mm ²		Lead
AWG size	20	SCIP number	C0979fba-9907-458f-a94a-db781440f273
Contact type	Turned gold plated	Approvals / Standards	
Further technical details		Certifications	CSA, EAC
Weight	0,72 g	UL	ECBT2
Operating temperature range (min, max)	-40°C ... +125°C	General ordering information	
Conductors stripping length	8 mm	EAN13 code	8015747015561
		eCl@ss 8.1	27440204
		ETIM 7.0	EC000796
		Packaging Information	
		Packaging length	112,00 mm
		Packaging height	95,00 mm
		Packaging width	117,00 mm
		Packaging weight	1,21 kg
		Packaging volume	1,24 dm ³
		Packaging description	Carton box
		Packaging quantity	1600 Pcs
		Packaging EAN code	8015747206945
		Sub-packaging length	50,00 mm
		Sub-packaging height	44,00 mm
		Sub-packaging width	50,00 mm
		Sub-packaging weight	0,15 kg
		Sub-packaging volume	0,11 dm ³
		Sub-packaging description	Plastic box
		Sub-packaging quantity	200 Pcs
		Sub-packaging EAN barcode	8015747015578

Part number

CDMD 0.5



Catalogue drawings



CDF and CDM contacts

conductor section mm ²	conductor slot $\varnothing A$ (mm)	conductors stripping length B (mm)
0,14-0,37	0,9	8
0,5	1,1	8
0,75	1,3	8
1,0	1,45	8
1,5	1,8	8
2,5	2,2	6