


Part number

CTF 10 R



Female insert, CT series, screw terminal connection, 10 poles + PE, 16 A 230/400 V 4 kV 2, size "57.27", with incorporated terminal block, right side mounting

| Product description | |
|---|---|
| Product type | Insert |
| Series | CT |
| Connection type | Screw terminal connection |
| Gender | Female |
| N. of poles | 10 poles + |
| Size | Size 57.27 |
| Specification | Right side mounting With incorporated terminal block |
| Technical data | |
| Current | 16 A |
| Voltage | 230 - 400 V |
| Rated impulse withstand voltage | 4 kV |
| Pollution degree | 2 |
| Rated voltage according to UL/CSA | 600 V |
| Wire cross-section | 0,75 mm ² - 2,50 mm ² |
| AWG size | 18 - 14 |
| Contact type | Turned silver plated |
| IP degree of protection | IP20 without enclosure, IP66/IP69 with enclosure |
| Further technical details | |
| Characteristics according to EN 61984 | 10A 230/400V 4kV 3; 10A 400V 4kV 2 |
| Mating cycles | ≥ 500 |
| Insulation resistance | ≥ 10 GΩ |
| Contact resistance | ≤ 4 mΩ |
| Weight | 130,00 g |
| Operating temperature range (min, max) | -40 °C ... +125 °C |
| Conductors stripping length | 12 mm |
| UL 94 flammability rating | V-0 |
| Torque for main contact | M2,6: 0,4 Nm; 3,5 lb.in (0,5 x 3 mm) |
| Tightening torque for PE connection | M4: 1,2 Nm, 10,6 lb.in (Ph2 or 1,0x5,5mm) |
| Tightening torque for fixing screws | M3: 0.5 Nm; 4.4 lb.in (Ph1 or 0.8x4 mm) |

| Material properties | |
|----------------------------------|--|
| Main material | Polycarbonate (PC) |
| Other materials | Contacts: copper alloy |
| Colour | RAL 7032 grey |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | 1a9c93ff-0445-4a16-81e3-1609ac5274d6 |
| Approvals / Standards | |
| Reference standard | EN 61984:2009-06 |
| Certifications | CSA, CQC, DNV, BV, EAC |
| UL | ECBT2 |
| General ordering information | |
| EAN13 code | 8015747040693 |
| eCl@ss 8.1 | 27440205 |
| ETIM 7.0 | EC000438 |
| Packaging Information | |
| Packaging length | 112,00 mm |
| Packaging height | 95,00 mm |
| Packaging width | 117,00 mm |
| Packaging weight | 0,56 kg |
| Packaging volume | 1,24 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 4 Pcs |
| Packaging EAN code | 8015747040709 |
| Sub-packaging weight | 0,14 kg |
| Sub-packaging description | Plastic packaging |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747040716 |

Part number

CTF 10 R



Catalogue drawings

