

Part number

CX 01 30PEAF



Female modular insert, Mixo series, screw terminal connections - 90° angled for cable lug, 1 pole, 2 modules, 300 A, PE module for earth termination

| Product description | | Material properties | |
|---|--|-------------------------------------|--|
| Product type | Modular insert | Main material | Polycarbonate |
| Series | Mixo | Other materials | Contacts: copper alloy |
| Connection type | Screw terminal connection | Colour | RAL 7032 grey |
| Gender | Female | RoHS conformity | Compliant with exemption 6(c); copper alloy containing up to 4% lead by weight |
| N. of poles | 1 PE pole | China RoHs - EFUP | 50 |
| Size | 2 modules | REACH SVHC substances | Yes Lead |
| Specification | For wire cross-section 16-120 mm ² PE angled MIXO Module | General ordering information | |
| Technical data | | EAN13 code | 8015747289900 |
| Current | 300 A | eCl@ss 8.1 | 27440205 |
| Rated impulse withstand voltage | 8 kV | ETIM 7.0 | EC000438 |
| Pollution degree | 3 | Packaging Information | |
| Contact type | Turned silver plated | Packaging weight | 0,63 kg |
| IP degree of protection | IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure | Packaging volume | 1,24 dm ³ |
| Further technical details | | Packaging description | Carton box |
| Mating cycles | ≥ 500 | Packaging quantity | 5 Pcs |
| Contact resistance | ≤ 3 mΩ | Packaging EAN code | 8015747290128 |
| Weight | 115,00 g | Sub-packaging length | 145,00 mm |
| Operating temperature range (min, max) | -40 °C ... +125 °C | Sub-packaging height | 89,00 mm |
| UL 94 flammability rating | V-0 | Sub-packaging width | 120,00 mm |
| | | Sub-packaging weight | 0,13 kg |
| | | Sub-packaging volume | 1,55 dm ³ |
| | | Sub-packaging description | Plastic bag |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747290135 |

Part number

CX 01 30PEAF



Catalogue drawings

