

Part number

# CX 01 9VM2



Male modular insert, Mixo Data series, D-SUB, 9 poles, 1 module, 5 A 50 V 0,8 kV 3, crimp, shielded, 2 cable entries

| Product description                           |  | Material properties                 |                      |
|---|--|-------------------------------------|----------------------|
| <b>Product type</b>                           | Modular insert   | <b>Main material</b>                | Polycarbonate (PC)   |
| <b>Series</b>                                 | Mixo Data  | <b>Colour</b>                       | RAL 7032 grey        |
| <b>Connection type</b>                        | D-SUB  | <b>RoHs conformity</b>              | Compliant            |
| <b>Gender</b>                                 | Male   | <b>China RoHs - EFUP</b>            | E                    |
| <b>N. of poles</b>                            | 9 poles  | <b>REACH SVHC substances</b>        | No                   |
| <b>Size</b>                                   | 1 module   | <b>General ordering information</b> |                      |
| <b>Specification</b>                          | 2 cable entries<br>Crimp, shielded                         | <b>EAN13 code</b>                   | 8015747271721        |
| <b>Technical data</b>                         |  | <b>eCl@ss 8.1</b>                   | 27440205             |
| <b>Current</b>                                | 5 A  | <b>ETIM 7.0</b>                     | EC000438             |
| <b>Voltage</b>                                | 50 V   | <b>Packaging Information</b>        |                      |
| <b>Rated impulse withstand voltage</b>        | 0,8 kV   | <b>Packaging length</b>             | 112,00 mm            |
| <b>Pollution degree</b>                       | 3  | <b>Packaging height</b>             | 95,00 mm             |
| <b>IP degree of protection</b>                | IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure | <b>Packaging width</b>              | 117,00 mm            |
| <b>Further technical details</b>              |  | <b>Packaging weight</b>             | 0,23 kg              |
| <b>Characteristics according to EN 61984</b>  | 5 A 50 V 0,8 kV 3  | <b>Packaging volume</b>             | 1,24 dm <sup>3</sup> |
| <b>Weight</b>                                 | 18,50 g  | <b>Packaging description</b>        | Carton box           |
| <b>Operating temperature range (min, max)</b> | -40°C...+70°C  | <b>Packaging quantity</b>           | 10 Pcs               |
|   |  | <b>Packaging EAN code</b>           | 8015747271738        |
|   |  | <b>Sub-packaging weight</b>         | 0,02 kg              |
|   |  | <b>Sub-packaging description</b>    | Plastic bag          |
|   |  | <b>Sub-packaging quantity</b>       | 1 Pcs                |
|   |  | <b>Sub-packaging EAN barcode</b>    | 8015747271745        |

Part number

**CX 01 9VM2**



Catalogue drawings

