

Part number

# CX 01 J8IM



Male modular insert, Mixo Data series, RJ45, 1 module, without connector, IDC

| Product description                           |  | Material properties                 |                      |
|---|--|-------------------------------------|----------------------|
| <b>Product type</b>                           | Modular insert   | <b>Main material</b>                | Polycarbonate (PC)   |
| <b>Series</b>                                 | Mixo Data  | <b>Colour</b>                       | RAL 7032 grey        |
| <b>Connection type</b>                        | RJ45   | <b>RoHs conformity</b>              | Compliant            |
| <b>Gender</b>                                 | Male   | <b>China RoHs - EFUP</b>            | E                    |
| <b>N. of poles</b>                            | 1 seat for RJ45 connector                                  | <b>REACH SVHC substances</b>        | No                   |
| <b>Size</b>                                   | 1 module   | <b>Approvals / Standards</b>        |                      |
| <b>Specification</b>                          | IDC<br>RJ45, adapter for Cat. 6A male IDC connector        | <b>Certifications</b>               | DNV, BV              |
| <b>Technical data</b>                         |  | <b>UL</b>                           | ECBT2                |
| <b>Current</b>                                | 1 A  | <b>cUL</b>                          | ECBT8                |
| <b>Rated voltage according to UL/CSA</b>      | 50 V   | <b>General ordering information</b> |                      |
| <b>IP degree of protection</b>                | IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure | <b>EAN13 code</b>                   | 8015747206198        |
| <b>Further technical details</b>              |  | <b>eCl@ss 8.1</b>                   | 27440205             |
| <b>Characteristics according to EN 61984</b>  | 1A 50V 0,8kV 3   | <b>ETIM 7.0</b>                     | EC000438             |
| <b>Insulation resistance</b>                  | ≥ 10 GΩ  | <b>Packaging Information</b>        |                      |
| <b>Contact resistance</b>                     | ≤ 3 mΩ   | <b>Packaging length</b>             | 112,00 mm            |
| <b>Weight</b>                                 | 12,30 g  | <b>Packaging height</b>             | 95,00 mm             |
| <b>Operating temperature range (min, max)</b> | -40°C...+70°C  | <b>Packaging width</b>              | 117,00 mm            |
| <b>UL 94 flammability rating</b>              | V-0  | <b>Packaging weight</b>             | 0,16 kg              |
|   |  | <b>Packaging volume</b>             | 1,24 dm <sup>3</sup> |
|   |  | <b>Packaging description</b>        | Carton box           |
|   |  | <b>Packaging quantity</b>           | 10 Pcs               |
|   |  | <b>Packaging EAN code</b>           | 8015747292122        |
|   |  | <b>Sub-packaging weight</b>         | 0,02 kg              |
|   |  | <b>Sub-packaging description</b>    | Plastic bag          |
|   |  | <b>Sub-packaging quantity</b>       | 1 Pcs                |
|   |  | <b>Sub-packaging EAN barcode</b>    | 8015747206365        |

Part number

# CX 01 J8IM



Catalogue drawings

|   |          |
|---|----------|
|   |          |
| Scale                                     | 1:1      |
| CX 01 J8IM<br>Male modular IDC RJ45 Cat.6 |          |
| Dimension in mm                           |          |
| Date                                      | 27/07/14 |
| Sign.                                     | Rafise   |

Diritti riservati All rights reserved