

Part number

CX 04 LF



Female modular insert, Mixo Data series, fibre optic, 4 poles, 1 module, for crimp contacts

Product description		Material properties	
Product type	Modular insert	Main material	Polycarbonate (PC)
Series	Mixo Data	Colour	RAL 7032 grey
Connection type	Fibre optic	RoHs conformity	Compliant
Gender	Female	China RoHs - EFUP	E
N. of poles	4 seats for fibre optic SC contacts	REACH SVHC substances	No
Size	1 module	Approvals / Standards	
Specification	For crimp contacts	Certifications	CSA, DNV, BV
Technical data		UL	ECBT2
Rated voltage according to UL/CSA	50V	cUL	ECBT8
IP degree of protection	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	General ordering information	
Further technical details		EAN13 code	8015747172264
Characteristics according to EN 61984	16A 830V 8kV 3 (aux: 16A 500V 6kV 3); 16A 1000V 8kV 2 (power contacts only)	eCl@ss 8.1	27440205
Insulation resistance	≥ 1 GΩ	ETIM 7.0	EC000438
Contact resistance	≤ 30 mΩ	Packaging Information	
Weight	8,70 g	Packaging length	180,00 mm
Operating temperature range (min, max)	-40°C ... +85°C	Packaging height	120,00 mm
UL 94 flammability rating	V-0	Packaging width	155,00 mm
		Packaging weight	0,69 kg
		Packaging volume	3,35 dm ³
		Packaging description	Carton box
		Packaging quantity	60 Pcs
		Packaging EAN code	8015747221191
		Sub-packaging length	35,00 mm
		Sub-packaging height	40,00 mm
		Sub-packaging width	155,00 mm
		Sub-packaging weight	0,12 kg
		Sub-packaging volume	0,22 dm ³
		Sub-packaging description	Carton tray
		Sub-packaging quantity	10 Pcs
		Sub-packaging EAN barcode	8015747172288



Part number

CX 04 LF





Catalogue drawings

CX 04 LF / LM




M



F

1.



F



M