

Part number

CX7MA 16 XFP



Male crimp contact, CX7 series, 70 A, turned silver plated, wire cross section 16 mm², AWG 6 - 5, extra-flexible Class 6 conductor, finger-proof version

Product description		Material properties	
Product type	Crimp contact	Main material	Copper alloy
Series	CX7		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Gender	Male	RoHs conformity	
Specification	Finger-proof version	China RoHs - EFUP	50
Technical data		REACH SVHC substances	Yes Lead
Current	70 A	SCIP number	C0979fba-9907-458f-a94a-db781440f273
Wire cross-section	16,00 mm ²	Approvals / Standards	
AWG size	6 - 5	Certifications	CSA, EAC
Contact type	Turned silver plated	UL	ECBT2
Further technical details		cUL	ECBT8
Mating cycles	≥ 500	General ordering information	
Contact resistance	≤ 0,5 mΩ	EAN13 code	8015747183758
Operating temperature range (min, max)	-40°C ... +125°C	eCl@ss 8.1	27440204
Conductors stripping length	15 mm	ETIM 7.0	EC000796
		Packaging Information	
		Sub-packaging length	50,00 mm
		Sub-packaging height	44,00 mm
		Sub-packaging width	50,00 mm
		Sub-packaging volume	0,11 dm ³
		Sub-packaging description	Plastic box
		Sub-packaging quantity	16 Pcs
		Sub-packaging EAN barcode	8015747279208

Part number

CX7MA 16 XFP



Catalogue drawings

