


Part number

KI 6363 EB6



Interlocked switched socket-outlet, EB6 series, 2 poles + PE, 6 h (blue), 63 A, 200 ÷ 250 V, without fuse-carrier

Product description

Product type	Interlocked switched socket-outlet
Series	KI...EB6
N. of poles	2 poles + 
Clock position	6
Size	143x343 fixing plates FC xx53 TB
Cable entry	M40
Specification	Without fuse-carrier

Technical data

Current	63 A
Voltage	200 ÷ 250 V
IP degree of protection	IP66

Further technical details

Weight	2.740,00 g
Operating temperature range (min, max)	-25°C ... +40°C
IK rating (impact degree of protection)	IK10

Material properties

Colour	RAL 7035 grey, RAL 5015 blue
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	F6799547-ab84-42f2-938f-233ba663766d

Approvals / Standards

Reference standard	EN 60309-1, -2 e -4
---------------------------	---------------------

General ordering information

EAN13 code	8015747201230
-------------------	---------------

Packaging Information

Packaging weight	2,74 kg
Packaging description	Carton box
Packaging quantity	1 Pcs
Packaging EAN code	8015747201247
Sub-packaging length	150,00 mm
Sub-packaging height	188,00 mm
Sub-packaging width	430,00 mm
Sub-packaging weight	2,74 kg
Sub-packaging volume	12,13 dm ³
Sub-packaging description	Plastic packaging
Sub-packaging quantity	1 Pcs
Sub-packaging EAN barcode	8015747201254