


Part number

# KI 6365 EB6



Interlocked switched socket-outlet, EB6 series,  
3 poles + N + PE, 6 h (red), 63 A, 380 ÷ 415  
V, without fuse-carrier

Product description		Material properties	
<b>Product type</b>	Interlocked switched socket-outlet	<b>Colour</b>	RAL 7035 grey, RAL 3000 red
<b>Series</b>	KI...EB6		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>N. of poles</b>	3 poles + N + 	<b>RoHs conformity</b>	6(c): copper alloy containing up to 4% lead by weight
<b>Clock position</b>	6	<b>China RoHs - EFUP</b>	50
<b>Size</b>	143x343 fixing plates FC xx53 TB	<b>REACH SVHC substances</b>	Yes Lead
<b>Cable entry</b>	M40	<b>SCIP number</b>	F6799547-ab84-42f2-938f-233ba663766d
<b>Specification</b>	Without fuse-carrier	<b>Approvals / Standards</b>	
<b>Technical data</b>		<b>Reference standard</b>	EN 60309-1, -2 e -4
<b>Current</b>	63 A	<b>General ordering information</b>	
<b>Voltage</b>	380 ÷ 415 V	<b>EAN13 code</b>	8015747201292
<b>IP degree of protection</b>	IP66	<b>Packaging Information</b>	
<b>Further technical details</b>		<b>Packaging weight</b>	3,04 kg
<b>Weight</b>	2.890,00 g	<b>Packaging description</b>	Carton box
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C	<b>Packaging quantity</b>	1 Pcs
<b>IK rating (impact degree of protection)</b>	IK10	<b>Packaging EAN code</b>	8015747201308
		<b>Sub-packaging length</b>	150,00 mm
		<b>Sub-packaging height</b>	188,00 mm
		<b>Sub-packaging width</b>	430,00 mm
		<b>Sub-packaging weight</b>	3,04 kg
		<b>Sub-packaging volume</b>	12,13 dm <sup>3</sup>
		<b>Sub-packaging description</b>	Plastic packaging
		<b>Sub-packaging quantity</b>	1 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747201315